



(19)

(11) Publication number: **08169779 A**

Generated Document.

**PATENT ABSTRACTS OF JAPAN**(21) Application number: **06332338**(51) Intl. Cl.: **C04B 38/00 C04B 28/02 E21D 11/00**(22) Application date: **14.12.94**

(30) Priority:	(71) Applicant: <b>CHICHIBU ONODA CEMENT CORP</b>
(43) Date of application publication: <b>02.07.96</b>	(72) Inventor: <b>SHIRASAKA MASARU MORISHITA NOBUAKI NOGUCHI MASAOKI</b>
(84) Designated contracting states:	(74) Representative:

**(54) FOAMED MORTAR  
CAVITY FILLER****(57) Abstract:**

**PURPOSE:** To obtain an foamed mortar cavity filler not deteriorating foamability even in the case of use of an ordinary foaming agent, preventing the separation of materials without using a thickener and having satisfactory characteristics while using fly ash in combination with cement as a hardening material.

**CONSTITUTION:** Water is added to a mixed hardening material obtd. by mixing fly ash with cement in a weight ratio of 4:6 to 2:8 to prepare a slurry contg. 50-70wt.% water. This slurry is mixed and blended with a proper amt. of a foaming agent.

**COPYRIGHT: (C)1996,JPO**